

# ProStep® Safeline (SL)

**THE ONLY COMPANY  
IN AUSTRALIA WITH  
EVERY TACTILE  
SOLUTION**

## ProStep® SL - Safety Stair Nosing

**ProStep® SL features the ProStep® characteristics of high safety, ease of installation and durability it is manufactured from reinforced tempered aluminium extrusion, milled into a straight faced anodised finish to provide a long term, attractive safe solution.**

ProStep® SL includes the SafeLine range of anti-slip peel and stick tapes which combine aluminium oxide and a thick plastic carrier to provide a flexible yet durable anti-slip solution. The inserts are formulated to resist water, steam and detergent and will withstand continuous temperatures in the range -30°C to 120°C. ProStep® SL safety stair nosing are pre-cut to length and pre-drilled, and are supplied with fixing screws and star plugs.

ProStep® SL is designed to meet the requirements of AS1428.4 and is available with a range of high visibility SafeLine anti-slip inserts to provide a safe environment

### **DIMENSIONS:**

Designed to conform to the Australian Standards, ProStep® Safety Stair Nosings

- have a combined insert depth of 50mm.
- are supplied predrilled, counter sunk and cut to length, ready to install.

Product Range: ProStep® SL is available with either black, grey, yellow or combination SafeLine anti-slip inserts and are R13 rated to provide maximum safety.

### **FEATURES:**

- Designed and manufactured from reinforced tempered aluminum extrusion to provide maximum strength and long term durability.
- Supplied milled and anodized to provide an attractive and safe solution.
- Supplied with an R13 SafeLine anti-slip insert for maximum safety.
- Exceeds the anti-slip requirements of Australian Standards AS4586.
- Supplied pre-drill, counter sunk and cut to length, ready to install.
- Are supplied with all necessary stainless steel fixing screws and anchors to ensure longevity.
- Can be retro-fit on to concrete, ceramic tiles, timber, carpet(direct stick) and most other surfaces.
- Are easy to install with no fuss - ideal for home DIY applications.
- SafeLine inserts are available as spares and are easily replaced in the event of damage.



### **APPLICATIONS:**

ProStep® SL safety stair nosing is particularly suitable for pedestrian traffic in internal flooring surfaces prone to water or oil spillage such as: concrete and other hard surface applications, including direct stick carpet.

### **LUMINANCE CONTRAST:**

In accordance with the Australian Standards a minimum luminance contrast of 30% must be provided between the stair nosing and surrounding substrate. ProStep® SL is available in 3 basic colours which allow specifiers to select the most appropriate luminance contrast for any given application and aesthetic requirement.

### **COMPLIES WITH:**

1. AS/NZS 1428:4.2002 Design for access and mobility.
2. AS/NZS 4586:1999 Slip resistance classification for new pedestrian surface materials.

[www.cobbletac.com](http://www.cobbletac.com)



**MELBOURNE** 5 Mareno Rd, Tullamarine VIC 3043 **P** 1300 282 282 **F** +61 3 9334 2621  
**SYDNEY** Unit 23, 43-51 College St Gladesville NSW 2111 **P** 1300 282 679 **F** 1300 282 329  
**QUEENSLAND** Unit 4, 10 Dual Ave Warana QLD 4575 **P** 1300 282 753 **F** 1300 282 329